






























OBIEKT : Gorzelnia w Kochcicach				WYKAZ STALI W2									
ELEMENT : Elementy konstrukcyjne piwnicy				NR RYSUNKU : K3 K4									
WYKONAŁ:				DATA:									
Nr	Stal	φ	KSZTAŁT [mm]	DŁUG. PRETA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]							
						A-0 St0S		A-IIIIN RB500W					
						6	8	8	10	12	16	20	6
			schody w kawiarni										
1	A-IIIIN	8	100 	2,8	55			154,0					
1A	A-IIIIN	8	100 	3,2	35			112,0					
2 mb	A-IIIIN	6		650	1								
3 mb	A-IIIIN	10		60	1			60,0					
4	A-0	6	360 	1,22	50	61,0							
5	A-IIIIN	8	200 	0,91	55			50,1					
6	A-IIIIN	8	200 	1,2	60			72,0					
7	A-IIIIN	8		2,86	10			28,6					
8	A-IIIIN	8	100 	2,1	10			21,0					
9	A-IIIIN	8		1,6	10			16,0					
			pochylnia										
10	A-IIIIN	8		4,55	11			50,1					
11	A-IIIIN	8		4,6	11			50,6					
12	A-IIIIN	8		3	11			33,0					
13	A-IIIIN	8		5,75	11			63,3					
14	A-IIIIN	8	90 	2,18	11			24,0					
15	A-IIIIN	8	90 	1,68	22			37,0					
16	A-IIIIN	8	90 	1,98	11			21,8					
17	A-IIIIN	6		1,45	140								
18	A-IIIIN	8	200 	0,94	11			10,3					
			S1 szt.2										
20	A-IIIIN	12		2,86	8			22,9					
21	A-0	6	200 	1,06	36	38,2							
			S2 szt.1										
22	A-IIIIN	16		2,4	10			24,0					
23	A-0	6	630 	1,76	18	31,7							
			S3 szt.1										
30	A-IIIIN	20		3,95	10							39,5	
31	A-0	6	460 	1,76	36	63,4							
32	A-IIIIN	20		3,43	10							34,3	

OBIEKT : Gorzelnia w Kochcicach				WYKAZ STALI W2									
ELEMENT : Elementy konstrukcyjne piwnicy				NR RYSUNKU : K3 K4									
WYKONAŁ:				DATA:									
Nr	Stal	φ	KSZTAŁT [mm]	DŁUG. PRĘTA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]							
						A-0 St0S		A-IIIIN RB500W					
						6	8	8	10	12	16	20	6
			S4 szt.2										
33	A-IIIIN	12		2,75	12					33,0			
34	A-IIIIN	12		5,05	12					60,6			
35	A-IIIIN	12	sredn=280 obw=880 	0,98	80					78,4			

mb kg kg kg kg	194	0	744	60	195	24	74	0
	0,222	0,394	0,394	0,616	0,887	1,578	2,465	0,222
	43	0	293	37	173	38	182	0
	43		723					
kg	766							

UWAGA

WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH (metoda A wg PN-EN ISO 3766:2005)