
































OBIEKT : Gorzelnia w Kochcicach				WYKAZ STALI									
ELEMENT : Sropy w poz. 0,00				NR RYSUNKU : K5 K6									
WYKONAŁ:				DATA:									
Nr	Stal	φ	KSZTAŁT [mm]	DŁUG. PRETA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]							
						A-0 St0S		A-IIIIN RB500W					
						6	8	8	10	12	16	20	6
1 mb	A-IIIIN	12		58	1					58,0			
2	A-0	6		0,9	42	37,8							
3 mb	A-IIIIN	6		2100	1								2100,0
			Nadproże N1										
5	A-IIIIN	12		2,1	3					6,3			
6	A-0	6		1,64	13	21,3							
			Nadproże N2										
7	A-IIIIN	12		1,6	2					3,2			
8	A-0	6		1,3	13	16,9							
			Antresola (strop kawiarni)										
			B1										
12	A-IIIIN	16		12	2					24,0			
12A	A-IIIIN	16		11,04	2					22,1			
13	A-0	8		1	71		71,0						
14	A-IIIIN	16		4	1					4,0			
			B2										
15	A-IIIIN	16		8,2	4					32,8			
13	A-0	8		1	50		50,0						
14	A-IIIIN	16		4	1					4,0			
			B3										
16	A-IIIIN	16		6,9	4					27,6			
13	A-0	8		1	50		50,0						
14	A-IIIIN	16		4	1					4,0			
17	A-IIIIN	16		2,8	4					11,2			
13	A-0	8		1	18		18,0						
19	A-IIIIN	8		2,75	72			198,0					
20	A-IIIIN	6		10,8	11								
21	A-IIIIN	8		3	34			102,0					
22	A-IIIIN	8		5,2	33			171,6					
23	A-IIIIN	8		3,6	34			122,4					
24	A-IIIIN	8		3	44			132,0					
25	A-IIIIN	8		6,55	16			104,8					

OBIEKT : Gorzelnia w Kochcicach				WYKAZ STALI									
ELEMENT : Sropy w poz. 0,00				NR RYSUNKU : K5 K6									
WYKONAŁ:				DATA:									
Nr	Stal	φ	KSZTAŁT [mm]	DŁUG. PRETA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]							
						A-0 St0S		A-IIIN RB500W					
						6	8	8	10	12	16	20	6
26	A-IIIN	8	90  90	3,18	42			133,6					
27	A-IIIN	8	90  90	2,18	62			135,2					
11	A-IIIN	10	80  80	1,32	104				137,3				
11A	A-0	6	80  80	1,06	52	55,1							
30 pr rozdz	A-IIIN	8	 250 mb	250	1			250,0					

mb	131	189	1350	137	68	130	0	2100
kg	0,222	0,394	0,394	0,616	0,887	1,578	2,465	0,222
kg	29	75	532	85	60	205	0	466
kg	104		1347					
kg	1451							

UWAGA

WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH (metoda A wg PN-EN ISO 3766:2005)