






























OBIEKT : Gorzelnia w Kochcicach				WYKAZ STALI W2									
ELEMENT : Klatka schodowa wewnętrzna				NR RYSUNKU : K7 K8									
WYKONAŁ:				DATA:									
Nr	Stal	φ	KSZTAŁT [mm]	DŁUG. PRĘTA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]							
						A-0 St0S		A-IIIIN RB500W					
						6	8	8	10	12	16	20	25
1	A-IIIIN	8		3,47	9			31,2					
2	A-IIIIN	8		1,51	27			40,8					
3	A-IIIIN	8		1,3	54			70,2					
4	A-IIIIN	8		1,26	36			45,4					
5 mb	A-IIIIN	6		450	1								
6	A-IIIIN	8		2,1	54			113,4					
7	A-IIIIN	8		1,5	27			40,5					
8	A-IIIIN	8		2,93	18			52,7					
9	A-IIIIN	8		2,2	18			39,6					
10	A-IIIIN	8		1,66	18			29,9					
11	A-IIIIN	8		1,9	36			68,4					
12	A-IIIIN	8		2,6	18			46,8					
13	A-IIIIN	8		2,6	18			46,8					
15	A-IIIIN	8		1,58	36			56,9					
16	A-IIIIN	8		2,55	9			23,0					
17	A-IIIIN	8		3,65	9			32,9					
18	A-IIIIN	8		3	9			27,0					
19	A-IIIIN	8		1,9	9			17,1					
20	A-IIIIN	8		3,54	9			31,9					
21	A-IIIIN	8		1,5	9			13,5					
26	A-IIIIN	12		3,25	14					45,5			
27	A-IIIIN	16		2,85	28						79,8		
28	A-0	8		1,08	119		128,5						
30	A-IIIIN	10		1,32	105				138,6				
31	A-0	6		1,06	40	42,4							

OBIEKT : Gorzelnia w Kochcicach				WYKAZ STALI W2									
ELEMENT : Klatka schodowa wewnętrzna				NR RYSUNKU : K7 K8									
WYKONAŁ:				DATA:									
Nr	Stal	φ	KSZTAŁT [mm]	DŁUG. PRĘTA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]							
						A-0 St0S		A-IIIIN RB500W					
						6	8	8	10	12	16	20	25
			Nw1										
35	A-IIIIN	12	1600	1,6	4					6,4			
36	A-0	6	250  250	1	9	9,0							
			strop nad szybem windowym										
40 mb	A-IIIIN	12	58 mb	58	1					58,0			
35	A-IIIIN	12	1600	1,6	3					4,8			
42	A-0	6	670  670	2,18	9	19,6							
43	A-0	6	110  110	1,06	22	23,3							
44	A-0	6	110  110	0,74	22	16,3							
45	A-IIIIN	8	2750	2,75	32			88,0					

kg	mb	111	129	916	139	115	80	0	0	
	kg	0,222	0,394	0,394	0,616	0,887	1,578	2,465	3,851	
	kg	25	51	361	85	102	126	0	0	
	kg	75		674						
		749								

UWAGA

WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH (metoda A wg PN-EN ISO 3766:2005)