









OBIEKT : Gorzelnia w Kochcicach				WYKAZ STALI W2									
ELEMENT : Szyb windy wieży				NR RYSUNKU : K11									
WYKONAŁ:				DATA:									
Nr	Stal	φ	KSZTAŁT [mm]	DŁUG. PRETA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]							
						A-0 St0S		A-IIIIN RB500W					
						6	8	8	10	12	16	20	25
1	A-IIIIN	12	4500	4,5	18					81,0			
2	A-IIIIN	10	4150	4,15	60				249,0				
3	A-IIIIN	12	4000	4	84					336,0			
4	A-IIIIN	10	3900	3,9	434				1692,6				
5	A-IIIIN	12	3620	3,62	18					65,2			
6	A-IIIIN	10	3620	3,62	60				217,2				
7 mb	A-IIIIN	8	2100 mb	2100	1			2100,0					
10	A-IIIIN	8	200 	1	816			816,0					
11	A-0	6	200 	1,76	30	52,8							
20	A-0	6	50 	0,31	550	170,5							
21	A-IIIIN	12	500 	3,17	64					202,9			
22	A-IIIIN	12	500 	3,03	36					109,1			
23	A-0	6	200 	0,9	196	176,4							
24	A-IIIIN	12	2000	2	6					12,0			
25	A-0	8	1160 	2,86	18		51,5						
26	A-0	8	1320 	3,18	9		28,6						
30	A-IIIIN	8	2000	2	12			24,0					
31	A-IIIIN	8	2000	2	11			22,0					

kg	mb	400	80	2962	2159	806	0	0	0	
	kg	0,222	0,394	0,394	0,616	0,887	1,578	2,465	3,851	
	kg	89	32	1168	1330	715	0	0	0	
	kg	120		3214						
	kg	3334								

UWAGA

WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH (metoda A wg PN-EN ISO 3766:2005)