

Krawężnik betonowy 15x22x100cm

5 15 15

Podsypka cem.-piaskowa (1:4) gr. 5cm

-0.03 ±0.00 +0.01

22 15 5 30 35

Lawa betonowa z betonu C12/15

Krawężnik betonowy
15x30x100cm

15 15 5

+0.01 ±0.00 ±0.00

15 35

30 15 5

Lawa betonowa
z betonu C12/15

35

Podsyпка cem.-piaskowa (1:4)
gr. 5cm

Poc.
gr.

Technical drawing showing a cross-section of a concrete curb (Obrzeże chodnikowe) with dimensions and material specifications:

- Obrzeże chodnikowe 8x30x100cm**: Concrete curb dimensions.
- Podsyпка cem.-piaskowa (1:4) gr. 3cm**: Cement-sand bedding (1:4 ratio, 3cm thickness).
- Ława betonowa z betonu C8/10**: Concrete base (C8/10 concrete).
- Dimensions**:
 - Top width: 38 cm
 - Base width: 21 cm
 - Overall height: 103 cm
 - Base height: 23 cm
 - Top layer height: 30 cm
 - Bedding height: 10 cm
 - Vertical offsets: -0.03, ±0.00, -0.03

The diagram illustrates the construction details of a concrete curb and its supporting base. Key features include:

- Krawężnik betonowy 15x30x100cm**: A precast concrete curb with a height of 15 cm.
- Ława betonowa z betonu C12/15**: A cast-in-place concrete base made of C12/15 concrete, with a total height of 35 cm from the subgrade.
- Podsyпка cem.-piaskowa (1:4) gr. 5cm**: A 5 cm thick bedding layer of cement-sand (1:4 ratio).
- Dimensions**: The curb has a top width of 30 cm. The base has a bottom width of 30 cm. Vertical dimensions show a 15 cm curb height and a 35 cm base height. Horizontal dimensions show offsets of 5 cm, 15 cm, and 15 cm from the centerline.
- Elevations and Slope**: The curb top is at elevation +0.01. The base top surface is at elevation ±0.00, sloping downwards at -0.12 towards the left side.

Krawężnik betonowy
15x30x100cm

Ława betonowa
z betonu C12/15

Podsyпка cem.-piaskowa (1:4)
gr. 5cm

5 15 15

±0.00 ±0.01

-0.12

30 15 35


30

Technical cross-section drawing of a concrete curb (Ława betonowa) with dimensions and material specifications:

- Dimensions:**
 - Top width: 5, 15, 15
 - Left side height: 22, 15, 5
 - Right side height: 12, 30
 - Bottom width: 35
- Materials and Layers:**
 - Krawężnik betonowy 15x22x100cm (Concrete curb 15x22x100cm)
 - Podsyпка cem.-piaskowa (1:4) gr. 5cm (Cement-sand bedding (1:4) 5cm thick)
 - Ława betonowa z betonu C12/15 (Concrete curb made of C12/15 concrete)
- Levels:**
 - 0.03
 - ±0.00
 - +0.01

Diagram showing a cross-section of a concrete structure with the following dimensions and materials:

- Opornik betonowy 12x25x100cm
- Podsyypka cem.-piaskowa (1:4) gr. 5cm
- Ława betonowa z betonu C8/10
- Ława betonowa z betonu C12/15
- Dimensions: 5, 12, 15, 25, 15, 5, 10, 20, 32, +0.01, +0.00



62-510 Konin, ul. Górnicza 6/18 • T/F +48 63 242 28 06 • REGON 310508247 • NIP 665-002-45-05 • eM pppbprobudkonin@op.pl