

## Program LEQ Professional - dane do obliczeń

Zał. H4'

Dane do obliczeń :  
\*\*\*\*\*

Współczynnik gruntu (całego obszaru analizy)-global G = 0.500  
Temperatura otoczenia 10[°C ]

Źródła punktowe

Nr	X[m]	Y[m]	z[m]	Pma	Symbol
1	694.0	627.2	7.5	77.9	E1
2	698.0	636.8	7.5	77.9	E2
3	704.4	641.6	7.5	77.9	E3
4	708.0	651.2	7.5	77.9	E4
5	716.0	656.0	7.5	77.9	E5
6	718.4	665.2	7.5	77.9	E6
7	726.0	670.4	7.5	77.9	E7
8	730.4	680.0	7.5	77.9	E8
9	737.6	685.2	7.5	77.9	E9
10	740.8	694.0	7.5	77.9	E10
11	748.0	699.6	7.5	77.9	E11
12	752.0	709.2	7.5	77.9	E12
13	750.9	718.1	1.8	0.0	E13
14	752.2	716.9	1.8	0.0	E14
15	753.8	716.6	1.8	0.0	E15
16	754.7	715.6	1.8	0.0	E16
17	760.2	711.6	1.8	0.0	E17
18	761.1	711.0	1.8	0.0	E18
19	762.1	710.0	1.8	0.0	E19
20	763.0	709.6	1.8	0.0	E20
21	716.4	611.2	7.5	77.9	E21
22	719.2	620.0	7.5	77.9	E22
23	726.4	625.6	7.5	77.9	E23
24	729.6	634.8	7.5	77.9	E24
25	737.6	640.0	7.5	77.9	E25
26	740.4	648.4	7.5	77.9	E26
27	747.6	653.6	7.5	77.9	E27
28	752.0	662.8	7.5	77.9	E28
29	759.6	668.0	7.5	77.9	E29
30	761.6	677.6	7.5	77.9	E30
31	770.0	682.8	7.5	77.9	E31
32	772.8	692.4	7.5	77.9	E32
33	773.0	701.7	1.8	0.0	E33
34	774.2	701.0	1.8	0.0	E34
35	775.5	699.8	1.8	0.0	E35
36	776.8	698.6	1.8	0.0	E36
37	782.3	694.5	1.8	0.0	E37
38	783.6	693.8	1.8	0.0	E38
39	784.7	692.9	1.8	0.0	E39
40	785.7	691.9	1.8	0.0	E40
41	737.2	593.6	7.5	77.9	E41
42	742.0	603.6	7.5	77.9	E42
43	749.2	608.0	7.5	77.9	E43

44	753.2	617.2	7.5	77.9	E44
45	759.6	623.2	7.5	77.9	E45
46	763.2	632.8	7.5	77.9	E46
47	772.4	637.2	7.5	77.9	E47
48	774.4	646.8	7.5	77.9	E48
49	781.6	652.4	7.5	77.9	E49
50	784.8	660.8	7.5	77.9	E50
51	793.2	666.0	7.5	77.9	E51
52	796.0	675.6	7.5	77.9	E52
53	795.3	684.5	1.8	0.0	E53
54	796.8	683.8	1.8	0.0	E54
55	797.8	682.8	1.8	0.0	E55
56	799.1	681.9	1.8	0.0	E56
57	804.0	677.8	1.8	0.0	E57
58	805.6	676.9	1.8	0.0	E58
59	806.6	675.9	1.8	0.0	E59
60	807.7	675.6	1.8	0.0	E60
61	756.5	601.0	2.5	97.0	AGR
62	653.6	616.3	1.5	73.0	P1
63	675.4	630.0	1.5	73.0	P2
64	696.7	658.8	1.5	73.0	P3
65	713.8	681.0	1.5	73.0	P4
66	735.0	709.8	1.5	73.0	P5
67	759.3	715.5	1.5	79.7	P6
68	781.4	699.1	1.5	79.7	P7
69	802.7	683.7	1.5	79.7	P8
70	803.1	660.5	1.5	73.0	P9
71	784.3	636.2	1.5	73.0	P10
72	764.4	610.1	1.5	73.0	P11
73	746.5	586.0	1.5	73.0	P12
74	725.0	580.2	1.5	73.0	P13
75	698.9	590.2	1.5	73.0	P14
76	680.4	605.9	1.5	73.0	P15
77	757.1	712.5	7.5	77.9	E61
78	779.0	695.4	7.5	77.9	E62
79	802.2	678.1	7.5	77.9	E63

Źródła typu hala produkcyjna :

WSPÓŁRZĘDNE WIERZCHOŁKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
1	683.5	631.4	698.1	620.8	760.8	705.0	746.8	714.8	0.0	7.0
2	705.6	615.2	720.2	604.0	783.5	688.2	768.6	698.9	0.0	7.0
3	728.0	597.8	742.9	587.2	805.9	671.4	791.3	682.1	0.0	7.0

POZIOMY HAŁASU i IZOLACYJNOŚĆ PRZEGRÓD

Nr	źródła		A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
1	sc.1	L wew	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

sc.4	L wew	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
dach	L wew	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr źródła		A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
2	sc.1 L wew	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2 L wew	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3 L wew	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4 L wew	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach L wew	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr źródła		A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
3	sc.1 L wew	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2 L wew	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3 L wew	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4 L wew	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach L wew	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

#### Punkty obserwacji

Nr	Symbol	X[m]	Y[m]	z[m]
1		670.4	568.8	4.0
2		1012.0	822.8	4.0
3		826.4	1013.2	4.0
4		466.8	371.6	4.0