

Program LEQ Professional - dane do obliczeń

ZAŁ. H1'

Dane do obliczeń :

Współczynnik gruntu (całego obszaru analizy)-global G = 0,800

Temperatura otoczenia 10[°C]

Źródła punktowe

Nr	X[m]	Y[m]	z[m]	Pma	Symbol
1	493.7	674.0	1.8	79.9	E-1
2	488.6	669.4	1.8	79.9	E-2
3	484.1	666.3	1.8	79.9	E-3
4	480.1	664.0	1.8	79.9	E-4
5	476.0	660.8	1.8	79.9	E-5
6	471.6	657.4	1.8	79.9	E-6
7	467.4	654.5	1.8	79.9	E-7
8	462.8	651.0	1.8	79.9	E-8
9	458.4	648.2	1.8	79.9	E-9
10	454.2	644.8	1.8	79.9	E-10
11	449.8	642.0	1.8	79.9	E-11
12	437.9	633.2	1.8	79.9	E-12
13	432.7	629.1	1.8	79.9	E-13
14	427.8	626.2	1.8	79.9	E-14
15	422.5	622.3	1.8	79.9	E-15
16	418.0	619.0	1.8	79.9	E-16
17	413.2	615.3	1.8	79.9	E-17
18	408.6	611.8	1.8	79.9	E-18
19	413.3	603.3	1.4	87.0	E-19
20	409.1	608.8	1.4	87.0	E-20
21	669.7	628.1	8.4	80.9	E-21
22	655.9	630.8	8.4	80.9	E-22
23	641.5	629.7	8.4	80.9	E-23
24	627.9	632.2	8.4	80.9	E-24
25	613.8	631.0	8.4	80.9	E-25
26	600.1	633.5	8.4	80.9	E-26
27	586.2	632.6	8.4	80.9	E-27
28	572.1	635.1	8.4	80.9	E-28
29	557.8	634.0	8.4	80.9	E-29
30	544.2	636.4	8.4	80.9	E-30
31	675.9	635.0	1.8	87.0	E-31
32	675.9	633.4	1.8	87.0	E-32
33	675.4	631.8	1.8	87.0	E-33
34	675.4	630.2	1.8	87.0	E-34
35	675.0	626.2	1.8	87.0	E-35
36	675.0	624.2	1.8	87.0	E-36
37	675.0	622.5	1.8	87.0	E-37
38	674.8	620.9	1.8	87.0	E-38
39	675.4	631.8	3.5	87.0	E-39
40	675.4	630.2	3.5	87.0	E-40
41	675.0	627.4	3.5	87.0	E-41
42	675.1	626.0	3.5	87.0	E-42
43	667.6	592.4	8.4	80.9	E-43

44	653.5	594.6	8.4	80.9	E-44
45	639.3	593.5	8.4	80.9	E-45
46	625.4	596.2	8.4	80.9	E-46
47	611.4	595.0	8.4	80.9	E-47
48	597.7	597.5	8.4	80.9	E-48
49	583.4	596.7	8.4	80.9	E-49
50	570.3	599.1	8.4	80.9	E-50
51	555.4	597.8	8.4	80.9	E-51
52	541.8	600.6	8.4	80.9	E-52
53	673.5	600.7	1.8	87.0	E-53
54	673.4	599.1	1.8	87.0	E-54
55	673.4	597.5	1.8	87.0	E-55
56	673.4	596.2	1.8	87.0	E-56
57	672.9	591.0	1.8	87.0	E-57
58	672.9	589.4	1.8	87.0	E-58
59	672.9	587.9	1.8	87.0	E-59
60	672.7	586.3	1.8	87.0	E-60
61	673.2	594.6	3.5	87.0	E-61
62	673.5	595.9	3.5	87.0	E-62
63	672.9	591.1	3.5	87.0	E-63
64	672.9	589.4	3.5	87.0	E-64
65	540.6	588.1	2.5	91.0	AGR
66	692.4	646.4	1.5	76.8	P1
67	680.4	629.6	1.5	74.8	P2
68	668.4	611.2	1.5	71.0	P3
69	679.6	592.4	1.5	73.6	P4
70	636.4	613.6	1.5	71.0	P5
71	603.2	616.4	1.5	77.3	P6
72	575.2	615.2	1.5	71.0	P7
73	546.0	616.8	1.5	79.7	P8
74	534.4	636.8	1.5	70.6	P9
75	533.6	599.6	1.5	73.3	P10
76	508.4	583.2	1.5	71.0	P11
77	467.6	583.6	1.5	71.0	P12
78	430.4	593.2	1.5	77.3	P13
79	406.8	602.8	1.5	73.6	P14
80	445.2	615.2	1.5	77.3	P15
81	480.8	628.0	1.5	77.3	P16
82	499.6	655.6	1.5	71.0	P17
83	520.0	669.6	1.5	77.3	P18
84	540.4	654.0	1.5	77.3	P19
85	574.4	651.6	1.5	71.0	P20
86	607.2	649.6	1.5	71.0	P21
87	642.0	647.2	1.5	71.0	P22
88	671.2	646.0	1.5	77.3	P23
89	676.1	636.1	1.8	87.0	EA1
90	675.0	620.3	1.8	87.0	EA2
91	673.2	601.2	1.8	87.0	EA3
92	672.8	585.4	1.8	87.0	EA4

Źródła typu hala produkcyjna :

WSPÓŁRZĘDNE WIERZCHOŁKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
1	494.0	673.2	501.7	664.1	415.4	600.9	407.6	610.6	0.0	4.8

2	541.4	645.5	540.2	625.7	675.1	618.6	676.1	638.8	0.0	7.7
3	538.6	609.5	673.5	603.3	672.4	583.1	537.8	589.8	0.0	7.7

POZIOMY HAŁASU i IZOLACYJNOŚĆ PRZEGRÓD

Nr źródła			A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
1	sc.1	L wew	75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
dach	L wew	75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr źródła			A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
2	sc.1	L wew	75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
dach	L wew	75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr źródła			A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
3	sc.1	L wew	75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
dach	L wew	75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Punkty obserwacji

Nr	Symbol	X[m]	Y[m]	z[m]
1		542.8	676.0	4.0
2		587.0	901.8	4.0
3		352.7	760.2	4.0
4		229.4	763.1	4.0
5		511.8	353.8	4.0

