

Legenda:

- projektowana nawierzchnia bitumiczna
- projektowane pobocze z kruszywa naturalnego
- krawędź nawierzchni
- krawędź poboczy

W-1 0+032,27	
X= 5822458,65	Y= 4529432,21
R=250	α=6,6666°
PW	m
SW	m
PSK	m
P _w =Pz	m
i	%

W-2 0+130,97	
X= 5822412,03	Y= 4529519,24
R=80	α=18,7146°
PW	m
SW	m
PSK	m
P _w =Pz	m
i	%

W-3 0+170,46	
X= 5822383,99	Y= 4529547,26
R=240	α=4,7680°
PW	m
SW	m
PSK	m
P _w =Pz	m
i	%

W-7 0+476,42	
X= 5822489,03	Y= 4529707,85
R=600	α=1,9388°
PW	m
SW	m
PSK	m
P _w =Pz	m
i	%

W-8 0+604,64	
X= 5822606,97	Y= 4529758,15
R=137	α=13,0679°
PW	m
SW	m
PSK	m
P _w =Pz	m
i	%

W-6 0+371,28	
X= 5822391,10	Y= 4529669,57
R=400	α=3,4866°
PW	m
SW	m
PSK	m
P _w =Pz	m
i	%

W-5 0+284,38	
X= 5822308,92	Y= 4529632,13
R=5	α=113,1421°
PW	m
SW	m
PSK	m
P _w =Pz	m
i	%

W-4 0+215,94	
X= 5822349,49	Y= 4529576,93
R=70	α=14,4349°
PW	m
SW	m
PSK	m
P _w =Pz	m
i	%

km 0+194
Proj. przepust $\varnothing$ 160mm L=9,00m
zakończony studnia, z wpustem

